



Series 40R, 39R & 33 Actuator Identification Chart

FIELD A SIZE

DIGITS 1 & 2			
05	Norbro Actuator	30	Norbro Actuator
10	Norbro Actuator	33	Norbro Actuator
15	Norbro Actuator	35	Norbro Actuator
20	Norbro Actuator	40	Norbro Actuator
25	Norbro Actuator	42	Norbro Actuator

FIELD C PRODUCT SERIES

DIGITS 7 & 8	
40	40R Series female drive
39	39R Series male drive
33	33 Series female drive 180°

FIELD E VARIATIONS

DIGIT 14 - PINION		
CODE	TOP	BOTTOM
E	Female Norbro square	Namur slot/tapping
M	Male Norbro square	Namur slot/tapping
N	Female 45° square (DIN/ISO)	Namur slot/tapping

DIGIT 15 - STANDARD OPTIONS	
0	If not used
H	Hydraulic

DIGIT 17 - REVISION	
---------------------	--

A		B				C		D				E				
SIZE		ROTATION				PRODUCT SERIES		FINISH				PINION DRIVE		REVISION		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17

FIELD B VARIATIONS

DIGIT 4 - ROTATION	
R	40R - European 96° / UK 92° 39R - 94.4° 33R - 180°

DIGIT 5 - BODY	
D	Standard (includes DIN/ISO location ring Namur top mounting pattern, metric tappings)
K	As D without ISO/DIN location ring
C	Namur top mounting pattern, UNC tappings

DIGIT 6 - FUNCTION	
A	Double acting
B	Spring return 10 springs
C	Spring return 8 springs
D	Spring return 6 springs
E	Spring return 4 springs
F	Spring return 2 springs (05 only)

FIELD D VARIATIONS

DIGIT 10 -FINISH	
1	Standard gold body / black end caps-anodised
2	Epoxy coated
3	PVC coated

DIGIT 11 - TEMPERATURE	
S	Standard -20°C to +100°C
H	High temperature -20°C to +150°C
L	Low temperature -40°C to 85°C

DIGIT 12 - INLET ENDCAP (05 MANIFOLD)	
D	Standard Namur pattern
G	Norbro pattern (obsolete)
K	Access (US)
S	Special large port

DIGIT 13 - SWITCH ENDCAP	
1	Standard metric tapping for J-Switch switchbox
2	Unified tapping for J-Switch switchbox
B	Blank
0	05 Actuators (Blank endcaps)
M	Metric limit stops (standard with DIN drive)