


NON HAZARDOUS (WEATHERTIGHT)

MONOSTABLE

PneuLINK™ linear system is manufactured from 316 stainless steel and brass materials. The ergonomic design ensures an easy set up, trouble free installation and maintenance free operation. The **PneuLINK™** dynamic mechanism is both self-compensating and self-aligning, with minimal backlash and hysteresis, for high repeatability and total reliability.

The **Valve Control Monitor (VCM)** acts as an integral junction box, which facilitates a single multi-core cable for the discrete inputs (DI), and the low power solenoid discrete output (DO), reducing site cabling and installation costs. **PneuLINK™** linear **Valve Control Monitor** system offers total installation flexibility and can be fitted in various pre-selected positions (refer page 3 & 4).



NON HAZARDOUS (WEATHERTIGHT)

FEATURES AND BENEFITS

- IP66/67 engineered resin enclosure ensures both strength and corrosion resistance for installation in harsh environments.
- Temperature rating: $-20^{\circ} \leq T_{amb} \leq +60^{\circ}C$
- Beacon shaped visual indication provides 360° visual feedback of valve OPEN (Black) or CLOSED (Yellow) positions.
- Black / Yellow colours, as a visual indicator, offers high visibility integrity, and is colour impaired friendly.
- Touch set cams are hand adjustable, spring loaded and self-locking, providing quick calibration of position switches and sensors.
- SPDT mechanical switches or inductive proximity sensors.
- Switch centralization plate allows for the accurate setting of switches, improved repeatability, and minimises hysteresis.
- NAMUR VDI/VDE standard mounting arrangement.
- Quick release design of terminal strip bracket allows removal of the terminal strip, which is pre-wired and numbered, to aid field wiring at commissioning and installation stage.
- M20 conduit entries fitted with IP rated plugs as standard to avoid ingress during site storage and transportation prior to installation.
- Extra conduit for easy field wiring as standard.
- SOV with red pneumatic “activated” indicator as standard.
- Solenoid coil integrated within the VCM housing, and is available with a choice of coil voltages.
- Choice of aluminium or 316 stainless steel solenoid valves, in 3 or 5 way configurations.
- Optional Cv ratings of 1.1 or 3.5
- Exhaust port flow regulators fitted as standard.

NON HAZARDOUS (WEATHERTIGHT)

TECHNICAL SPECIFICATION

The Valve Control Monitor contains two switches to indicate the fully open and closed positions of the valve – refer below options

STANDARD

V3 Mechanical Switches SPDT


Single Pole Double Throw–Form C

Resistive Loads

15A @ 250VAC
6A @ 24VDC
0.5A @ 125VDC
0.25A @ 250VDC

Inductive Loads

10A @ 250VAC
6A @ 24VDC
0.5A @ 125VDC
0.25A @ 250VDC





Note: Lamp & Motor loads refer **Dr Pneuton** for guidance!

OPTION 1

2 Wire Inductive Sensors

DC PNP/NPN, normally open / closed programmable

Operating Voltage 5...36VDC
Operating Current 4...200mA
Voltage Drop < 4.6V
Leakage Current < 0.8mA
Switching Frequency 2000Hz
Display Switching Status Yellow LED




OPTION 2

3 Wire Inductive Sensors

DC PNP normally open

Operating Voltage 10...30VDC
Operating Current 0...100mA
Voltage Drop < 3.0V
Leakage Current 0...0.5mA
Switching Frequency 0...1000Hz
Display Switching Status Yellow LED



SOV

Characteristics


Pneumatic Porting : G1/4" (standard) or G1/2"
Operating Pressure : 3.1–8.3 bar (g)
Air Quality : ISO 8573-1 Class 5
Flow Rate : 1100 NL/min (standard) or 3500 NL/min
Coil Class Insulation : H
Electrical Safety : IEC335
Duty Rating : 100%

Standard Voltages	Inrush ~ (VA)	Nominal ~ (VA)	Watts
24V DC (±10%)			< 2.0
110VAC / 50Hz (±10%)	10	5.0	
230VAC / 50Hz (±10%)	10	5.0	

Note : Other voltages and 60Hz are available on request

NON HAZARDOUS (WEATHERTIGHT)

LOGIC SELECTOR



Note: Typical standard logic applications illustrated, refer **Dr Pneuton** for any alternative requirements!

The default **double acting** actuator configuration is **Code 1**

The default **single acting** actuator configuration is **Code 3**

Option	Loss of air	Loss of power
1	Fail Last *	Fail Close with Motive Power
2	Fail Last *	Fail Open with Motive Power
3	Fail Close or Open Depending on Spring Configuration	Fail Close or Open Depending on Spring Configuration
4	Fail Close or Open Depending on Spring Configuration, with closed loop breather system †	Fail Close or Open Depending on Spring Configuration

* Valves in the fully open / closed position, with actuator vertically installed, may drift in the absence of motive power!

† Select the closed loop breather system for arduous environments, to refresh the non-pressurised side of the actuators piston on the spring strokes negative displacement, to prevent ingress - refer **Dr Pneuton** for guidance!




NON HAZARDOUS (WEATHERTIGHT)

CONFIGURATOR

The default VCM configuration is Code A.

It is important that the preferred configuration is defined at point of order.

Refer to optional configurations illustrated below.



Images shown from actuator end view



Pneuton

ENGINEERING VALVE AUTOMATION COMPLIANCE

PneuLINK™

VALVE CONTROL MONITOR

NON HAZARDOUS (WEATHERTIGHT)

Notes

